

Insert

Application	Picture	Designation	Coated							Uncoated	Dimensions (mm)					Configuration	Page			
			NC3120	NC3225	NC3225	NC5330	NC6315	PC5300	PC8110	PC9030	H01	b	r	l	d			t		
Face Grooving	FGD	FGD	300R-03									3.0	0.3	15.0	2.0	4.0		C36		
			400R-04										4.0	0.4	15.0	3.0		4.5	C37	
			500R-04											5.0	0.4	15.0		4.0	5.0	
	FGM	FGM	300R-03										3.0	0.3	15.0	2.0	4.0		C36	
			400R-04										4.0	0.4	15.0	3.0	4.5		C37	
			500R-04											5.0	0.4	15.0	4.0		5.0	
	FMM	FMM	300R-03										3.0	0.3	15.0	2.0	3.91		C36	
			400R-04										4.0	0.4	15.0	3.0	3.96		C37	
			500R-04											5.0	0.4	15.0	4.0		4.42	
Face Grooving	MFMN	MFMN	300									3.0	0.2	18.0	2.0	3.0		C35 C41		
Grooving · Turning	MGGN-M	MGGN-M	300-02-M									3.0	0.2	21.0	2.35	4.8		C30 C32 C34 C41		
			04-M										3.0	0.4	21.0	2.35			4.8	
			08-M										3.0	0.8	21.0	2.35			4.8	
			400-02-M										4.0	0.2	21.0	3.3			4.8	
			04-M										4.0	0.4	21.0	3.3			4.8	
			08-M										4.0	0.8	21.0	3.3			4.8	
			500-02-M										5.0	0.2	26.0	4.1			5.8	
			04-M										5.0	0.4	26.0	4.1			5.8	
			08-M										5.0	0.8	26.0	4.1			5.8	
			600-02-M										6.0	0.2	26.0	5.0			5.8	
			04-M										6.0	0.4	26.0	5.0			5.8	
			08-M										6.0	0.8	26.0	5.0			5.8	
Grooving	MGMN-G	MGMN-G	150-G									1.5	0.15	16.0	1.2	3.5		C30 C32 C34 C41		
			200-G										2.0	0.2	16.0	1.6			3.5	
			250-G											2.5	0.2	18.5			2.0	3.85
			300-G											3.0	0.3	21.0			2.35	4.8
			400-G											4.0	0.3	21.0			3.3	4.8
			500-G											5.0	0.5	26.0			4.1	5.8
			600-G											6.0	0.8	26.0			5.0	5.8
Grooving · Turning	MGMN-M	MGMN-M	200-M									2.0	0.2	16.0	1.6	3.5		C30 C32 C34 C41		
			250-M										2.5	0.2	18.5	2.0			3.85	
			300-02-M										3.0	0.2	21.0	2.35			4.8	
			300-M											3.0	0.4	21.0			2.35	4.8
			350-03-M											3.5	0.3	21.0			2.9	4.8
			400-02-M											4.0	0.2	21.0			3.3	4.8
			400-M											4.0	0.4	21.0			3.3	4.8
			500-04-M											5.0	0.4	26.0			4.1	5.8
			500-M											5.0	0.8	26.0			4.1	5.8
			600-M											6.0	0.8	26.0			5.0	5.8
			800-M											8.0	0.8	31.0			6.0	6.5

●: Stock item

